




Color Display Fingerprint Time Recording Access Controller

Key Features

Authentication

Fingerprint + PIN+ EM / Mifare Card (Optional)optional Access Control
Built–in Camera For Real Time Picture Taking & Built–in Mic. For Voice Recording
Multi Devices In Multi Regions Support Server And Client Connection
Backup Battery For 4 Hours Operation



Specifications	
Dimensions	L 198x W 128 x H 43mm
FRR	≤0.01%
■ FAR	≤0.0001%
FP Recognition Speed	1 sec
■ FP Template Capacity	5000 pc (Standard), 30,000 pc (Optional)
■ Transaction Memory Capacity	200,000 pc
■ Verification Modes	1:1 OR 1:N
Authentication Methods	FP, PIN, RFID Card (Optional)
Operation Mode	Standalone or connect with PC
Communications	RS232/485, TCP/IP, USB Drive
Operation Power	<5W
Power Input	DC 12V
Weight	1.2KG
Display	QVGA 76800 pixels color backlit LCD
■ Voice Input	Voice recording with built-in mic
■ Image Capture	Instant photo-taking with built-in camera
■ Image Display	Support image retrieval & display
Languages	Display : English/T. Chinese/S. Chinese
	Voice : English/Cantonese (Customization feasible)
Access Control Feature	Standard with Time Zone management
Alarm	Programmable alarm with signal output interface
■ Input method	T9 Chinese/English text input
Summer Daylight Saving	Standard feature
Attendance Checking	Any staff may check own attendance
■ Indication Feature	FP verification success/failure indication
■ Network Connectivity	Support multi machine connection over network
	and support server & client feature